

Dolphin 9900 Series

Mobile Computers

Dolphin 9900 mobile computers are purpose-built for robust mobile data collection and communication solutions – combining a rugged, user-friendly design with a complete suite of technologies to enable maximum mobile user productivity and efficiency.

Seamless connectivity between mobile workers and the enterprise is enabled through integrated wireless WAN and LAN communications for high-speed data transfer and cellular voice communication – anytime, anywhere. Bluetooth® connectivity to any compatible wireless device broadens the mobile worker's capabilities in the field.

Integrated Global Positioning System (GPS) technology enables location-based functionality such as turn-by-turn navigation, and route optimization, and the ability to document proof of visitation or service with a time and location stamp.

Adaptus® Imaging Technology 5.0 provides workers with the data capture functionality they need to get the job done quickly and efficiently – whether it is scanning a package for delivery confirmation, tracking inventory, electronically capturing a signature for proof of receipt, or taking a picture of damaged goods.

Just as important as the technologies the user puts to work, an innovative power management system ensures they get battery-life that lasts a full work-shift, even in wireless, scan-intensive environments.

Rugged, ergonomic and full-featured, the Dolphin 9900 mobile computer is the right choice where real-time information processing and solution reliability is critical to a company's operation.

Features

- s Optimal Combination of Industrial-Grade Durability and Usability:** Internal magnesium-alloy roll cage, environmentally sealed housing and specialized wear-resistant components deliver reliability in demanding mobile environments, while an ergonomic design provides comfortable and intuitive use.
- s Wireless Full Area Networking™ (WFAN):** Integrated multi-mode wireless technology includes GSM/E-GPRS and 802.11b/g for real-time data exchange and voice communications on-site or off, plus Bluetooth for efficient wireless connection to peripheral devices.
- s Built-In GPS Technology:** Enables turn-by-turn navigation, driver route optimization, "bread-crumbling," geo-fencing, and other location-based applications gives you a powerful tool to enhance the effectiveness of your mobile workforce and gives your enterprise better control over assets in the field.
- s Versatile, High Performance Data Collection:** Adaptus Imaging Technology 5.0 reads linear and 2D bar codes, captures digital images, and enables electronic signature capture - enabling workers to do more with a single device.
- s Shift-PLUS™ Power Management:** Powers scan intensive, real-time wireless applications continuously for 10 hours or more, enhancing productivity while greatly extending useful battery life and reducing replacement costs.
- s Windows Mobile® 6:** Industry-standard platform for developers and users ensures ease of integration and intuitive use.
- s User-Preferred Ergonomic Designs:** The flashlight and pistol-grip form factors facilitate comfortable, single-handed data collection for extended periods of use.

Dolphin 9900 Technical Specifications

System Architecture

Processor:	Intel XScale PXA270 624 MHz
Development Environment:	Honeywell SDK for Windows Mobile 6.0
Operating Platform:	Windows Mobile 6.0
Third-Party Software:	SOTI MobiControl (remote device management), PowerNet™ Terminal Emulation (TNVT, 3270, 5250), and ITScriptNet™
Memory:	256MB RAM X 1GB Flash
Keyboards:	Three in-mold, hard-top keyboard options: 35-key numeric-shifted alpha, 43-key alpha-shifted numeric, and 56-key full alpha/numeric

Data Inputs/Electrical

Imager/Scanner:	5300 Standard Range with High-Vis laser aimer, 5100 Standard Range & 5100 Smart Focus with green aimer Caution - use of controls or adjustments or performance of procedures other than those specified herein may result in hazardous radiation exposure.
1D Symbologies Read:	Codabar, Code 3 of 9, Code 11, Code 32 Pharmaceutical (PARAF), Code 93, Code 128, EAN with Add-On and EAN with Extended Coupon Code, EAN-13, Interleaved 2 or 5, Matrix 2 of 5, Plessey, PosiCode, GS1 Databar, Straight 2 of 5 IATA, Straight 2 of 5 Industrial, Telepen, Trioptic Code, UCC/EAN-128, UPC & UPC-A
2D Symbologies Read:	Aztec, Code 16K, Composite, Data Matrix, MaxiCode, OCR, PDF417, QR Code, GS1 Databar
Composite and OCR Codes:	Aztec Mesa, Codablock F, EAN-UCC, GS1 Databar-14 and OCR-A and OCR-B
Postal Codes:	Postnet, Australian, British, Canadian, China, Japanese, KIX (Netherlands), and Korea Post, Planet Code



Data Outputs

Display:	3.5 in. 1/4 VGA (240 x 320 portrait mode) color TFT LCD display with industrial-grade, polycarbonate touch panel
I/O Ports:	Industrial I/O connector supports USB 1.1 and serial RS-232 (115 Kbps) communication and charges via cradles, AC adapter cables, Integrated IrDA port, Integrated audio jack that acts as a speaker and a microphone
Mass Storage:	User-accessible Secure Digital memory interface supports memory cards up to 4GB and SDIO

Wireless Radio Options

WWAN (9900 only):	GSM Quad-band (850/900/1800/1900MHz) radio with accessible SIM card interface, GSM release 99, EDGE (E-GPRS) multi-slot Class 12, GPRS multi-slot Class 12
WLAN:	IEEE 802.11b/g
WLAN Security:	Wi-Fi Certified, WPA2, EAP, CCXv4, WEP, LEAP, TKIP, MD5, EAP-TLS, EAP-TTLS, WPA-PSK, PEAP
WPAN:	Bluetooth (Class 2)
GPS (9900 only):	Integrated GPS (Global Positioning System) receiver with internal antenna supporting SiRFstarIII technology

Physical

Dimensions	9900: Wide x Long x Deep: 3.4 in. (8.6 cm.) x 9.6 in. (24 cm.) x 2.1 in. (5.3 cm.) 9950: Wide x Long x Deep: 3.4 in. (8.6 cm.) x 9.6 in. (24 cm.) x 2.36 in. (6 cm) at display, 1.34 in. (3.4 cm) at grip
Weight	9900: 21.4 oz. (606g); 9950: 22.9 oz. (649g)
Operating Temperature	14° to 122°F (-10°C to 50°C); can operate down to -20°C with potential degradation in performance depending on the application
Storage Temperature	-4° to 158°F (-20° to 70°C)
Humidity	95% humidity, non-condensing
Electrical Static Discharge	15 KVA Air & 8 KVA Contact
Impact Resistance	Withstands multiple 5 ft. (1.5m) drops onto concrete. Exceeds 2000 3 ft. (1m) tumbles
Environmental Resistance:	Independently certified to meet IP64 standards for moisture and particle resistance
Power	2500mAh Extended-life, Li-ion battery pack with hot-swappable design for fast replacement in the field
Other	Integrated stylus with tether and removable hand strap

Regulatory Approvals

FCC-CE-Radio Country: US/Canada, R&TTE

Microsoft, Windows, and the Windows Logo are registered trademarks or trademarks of Microsoft Corporation. Intel is a registered trademark of Intel Corporation. The Bluetooth trademarks are owned by Bluetooth SIG, Inc. U.S.A. and licensed to Honeywell International Inc. Dolphin products have no affiliation with Honeywell branded batteries/chargers, which are exclusively distributed by Global Technology Systems pursuant to a license agreement.

Honeywell Security & Data Collection

Honeywell Scanning & Mobility
700 Visions Drive
Skaneateles Falls, NY 13153
800.582.4263
www.honeywell.com



For more information:

www.honeywell.com/aidc

Honeywell