GENKOTE

Technical Data Sheet

Product:

22 Adhesive

Description:

22 adhesive is a permanent acrylic pressure sensitive adhesive designed for clear film labels, overlays and graphic arts products.

Recommended Applications:

22 adhesive is designed for use on clear and opaque labels and decals. Typical face films include polypropylene, opaque polypropylene, cast polypropylene, polyethylene and polyester amongst other films.

Features:

- Excellent Clarity
- Good peel adhesion properties on a variety of surfaces
- Good tack
- Excellent water resistance
- Non-blushing
- Excellent heat resistance properties
- Pasteurizable
- Ice chest usable
- Good UV stability
- Good chemical Resistance properties
- Excellent for use in Beverage Label and Health & Beauty applications

Adhesive:

22 permanent

	<u>Value</u>	<u>Units</u>	ASTM Method
Loop Tack:	5	lbs/in ²	PSTC-16(SS)
Peel Adhesion			
20 minute:	4	lbs/in	PSTC-101(SS)
24 hour:	5	lbs/in	PSTC-101(SS)
Shear Adhesion:	Medium		PSTC-107(SS)

Minimum Application Temperature: 50 °F

Service Temperature Range: -40°F to +248°F (Adhesive Only; Substrate Dependent)

General Data Coated Products

4354 Ferguson Drive • Cincinnati, Ohio 45245 • Phone: 800-733-5252 x2374 • Fax: 513-752-6947 Email: solutions@general-data.com • Web: http://www.general-data.com MADE IN_THE USA



GENKOTE

Shelf Life:

Technical Data Sheet

One year under standard storage and humidity conditions. For maximum product longevity, store out of direct sunlight.

For product inquiries, please contact: Paula Becknell Sales Coordinator 800-733-5252 ext. 2374 pbecknell@general-data.com

Note: Values on this page are nominal - subject to normal industry variance.

PRODUCT DISCLAIMER

All labels and label material constructions are sold with the understanding that the purchaser has independently determined the suitability of each product for the application for which it is purchased. The seller disclaims any implied warranty of fitness of a product for a particular purpose. All materials should be tested thoroughly by the purchaser under end-use conditions to ensure they meet the requirements of a specific application.

General Data Coated Products

4354 Ferguson Drive • Cincinnati, Ohio 45245 • Phone: 800-733-5252 x2374 • Fax: 513-752-6947 Email: solutions@general-data.com • Web: http://www.general-data.com MADE IN_THE USA

ERTIFICS ISO 9001