

Technical Data Sheet

Product:

27 Adhesive

Description:

27 adhesive is a removable acrylic pressure sensitive adhesive that has good aging characteristics and shrink resistance.

Recommended Applications:

27 adhesive is designed for use on bumper sticker and punched vinyl window graphic applications. It is also used with a variety of films including vinyl, polyester and polypropylene.

Features:

- Good peel and shear
- Good plasticizer resistance

Adhesive:

27 removable

	<u>Value</u>	<u>Units</u>	<u>ASTM Method</u>
Loop Tack:	39.5	oz/in ²	PSTC-16(SS)
Peel Adhesion			
20 minute:	20	oz/in	PSTC-101(SS)
24 hour:	24.25	oz/in	PSTC-101(SS)
Shear Adhesion:	High		PSTC-107(SS)

Minimum Application Temperature: 50°F

Service Temperature Range: -40°F to +248°F
(Adhesive Only; Substrate Dependent)

Shelf Life:

One year under standard storage and humidity conditions. For maximum product longevity, store out of direct sunlight.

General Data Coated Products

4354 Ferguson Drive • Cincinnati, Ohio 45245 • Phone: 800-733-5252 x2374 • Fax: 513-752-6947
Email: solutions@general-data.com • Web: <http://www.general-data.com>

MADE IN THE USA



For product inquiries, please contact:
Paula Becknell
Sales Coordinator
800-733-5252 ext. 2374
pbecknell@general-data.com

Note: Values on this page are nominal – subject to normal industry variance.

PRODUCT DISCLAIMER

All labels and label material constructions are sold with the understanding that the purchaser has independently determined the suitability of each product for the application for which it is purchased. The seller disclaims any implied warranty of fitness of a product for a particular purpose. All materials should be tested thoroughly by the purchaser under end-use conditions to ensure they meet the requirements of a specific application.

General Data Coated Products

4354 Ferguson Drive • Cincinnati, Ohio 45245 • Phone: 800-733-5252 x2374 • Fax: 513-752-6947
Email: solutions@general-data.com • Web: <http://www.general-data.com>

MADE IN THE USA

