General Data
Smarter Technology. Exceptional Results.

CP-GK9-341C00

JET-KOTE™ DIGITAL INKJET PRINT RECEPTIVE PAPER AND FILM PRODUCTS
TECHNICAL DATA SHEET

PRODUCT NUMBER

CP-GK9-341C00

PRODUCT NAME

Jet-Kote Premium SG/Perm/40#sck

TYPE

Semi-Gloss IJ Paper

DESCRIPTION

A semi-gloss white paper designed to be compatible with most aqueous pigment and dye-based IJ inks, combined with a permanent hot melt adhesive and a 40#sck liner.

PRINT COMPATIBILITY

Aqueous pigment/dye inkjet

FACESTOCK

3.4 mil white semi-gloss inkjet receptive paper

	Value	Units	ASTM Method
Caliper:	3.4	mils	
Basis Weight:	21.7	lbs/ream	
Opacity:	90	percent	
Gloss (85°):	55	percent	
Brightness:	96.5		

ADHESIVE

Permanent

	Value	Units	ASTM Method
Loop Tack:	5.59	lbs/in^2	PSTC-16(Glass)
Peel Adhesion			
20 Minute:	6.1/PT	lbs/in	PSTC-101(Glass)
Shear Adhesion:	Medium		PSTC-107(SS)

Minimum Application Temperature: 35°F

Service Temperature Range: 0°F to +140°F

LINER

40# SCK

		Value	Units	ASTM Method
Caliper:		2.5	mil	
Basis Weight:		40	lbs/ream	
Tensile:	MD	40	lbf/in	D882
	CD	18	lbf/in	D882
Tear:	MD	30	percent	D882
	CD	35	percent	D882
Opacity:		89	percent	
Moisture:		4.5	percent	

SHELF LIFE

One year under standard storage and humidity conditions. For maximum product longevity, store out of direct sunlight and away from any fumes.

GENERAL DATA – COATED PRODUCTS DIVISION | 800-733-5252 x2374 | WWW.GENERAL-DATA.COM/COATING