

Material Specification Sheet**Product:**

M-241

Description:

A white topcoated polypropylene facestock with an all temperature acrylic adhesive and a super calendered semi-bleached kraft liner.

Recommended Applications:

This material is recommended for semi-rigid and rigid containers and prime labeling applications that require the durability and aesthetics of firm labels that may be applied at various temperatures.

Facestock:

A white topcoated polypropylene facestock that is semi conformable and designed for excellent printing, converting and label dispensing. It is recommended to test print and consult with your ink supplier to confirm use for your application. Not recommended for outdoor use.

		<u>Value</u>	<u>Units</u>
Caliper:		2.6	mil
Tensile:	MD	14	lbs/in
	CD	80	lbs/in
Elongation:	MD	12	%
	CD	45	%

Adhesive:

An all temp. acrylic adhesive that performs well in cold and damp environments as well as elevated temperatures.

		<u>Value</u>	<u>Units</u>
Thickness:		0.0007	in
Minimum Application temp:		-20	°F
Service temp:		-65 to +200	°F
Peel:		1.8	lbs/in

Liner:

A super calendered semi-bleached kraft liner that is coated with a release system that is designed specifically for label dispensing. Primarily for roll-to-roll applications.

		<u>Value</u>	<u>Units</u>
Basis Weight:		40	lbs/ream
Caliper:		2.5	mil

Shelf Life:

One year, under standard storage and humidity conditions

PRODUCT DISCLAIMER

All labels and label material constructions are sold with the understanding that the purchaser has independently determined the suitability of each product for the application for which it is purchased. The seller disclaims any implied warranty of fitness of a product for a particular purpose. All materials should be tested thoroughly by the purchaser under end-user conditions to ensure they meet the requirements of a specific application.

