

Material Specification Sheet**Product:**

M-552

Description:

A white matte-coated computer imprintable polyester film facestock with a clear acrylic dispersion permanent adhesive and a white kraft liner.

Recommended Applications:

This material is recommended for drum and logistics labeling.

Facestock:

A white matte-coated computer imprintable polyester film facestock.

	<u>Value</u>	<u>Units</u>
Basis Weight	53	lbs/ream
Caliper:	2.3	mil
Elongation: MD	150	%
CD	130	%
Brightness:	88	%

Adhesive:

A clear acrylic dispersion permanent adhesive with excellent clarity UV stability and water resistance.

	<u>Value</u>	<u>Units</u>
Minimum Application temp:	40	°F
Service temp:	-4 to +212	°F
Shear:	8	hours
Loop Tack:	5	N

Liner:

A white kraft liner.

	<u>Value</u>	<u>Units</u>
Basis Weight:	62	lbs/ream
Caliper:	3.2	mil
Tensile: MD	31	lbs/in

Shelf Life:

One year, under standard storage and humidity conditions

PRODUCT DISCLAIMER

All labels and label material constructions are sold with the understanding that the purchaser has independently determined the suitability of each product for the application for which it is purchased. The seller disclaims any implied warranty of fitness of a product for a particular purpose. All materials should be tested thoroughly by the purchaser under end-user conditions to ensure they meet the requirements of a specific application.

