

## Material Specification Sheet

Product:  
M-911

Description:

A hard clear polypropylene film with a permanent pressure-sensitive acrylic adhesive and a moisture stable polycoated layflat release liner.

Recommended Applications:

Recommended for applications such as bumper stickers, or where an alternative to vinyl facestocks are needed. Adheres well to a variety of surfaces including chrome-coated metal, chrome-coated plastic, glass, auto glass and painted plastic.

Facestock:

A hard clear polypropylene film with a topcoat that optimizes printability with solvent and UV screen inks. Alternative material to topcoated vinyl.

	<u>Value</u>	<u>Units</u>	<u>Test Method</u>
Caliper:	3.6	mil	ASTM D-3652
Dimen. Stability: MD	0.50		24 hour on aluminum panel/ 24 hour @ 160°F
TD	0.50		

Adhesive:

A permanent pressure-sensitive acrylic adhesive which bonds well to a variety of surfaces including chrome-coated metal or plastic, glass, auto glass and painted plastic.

	<u>Value</u>	<u>Units</u>	<u>Test Method</u>
Application temp:	50°	Fahrenheit	
Service temp:	-40° to +176°	Fahrenheit	

Liner:

A 90# moisture stable polycoated layflat release liner for ease of converting.

	<u>Value</u>	<u>Units</u>	<u>Test Method</u>
Caliper:	6.9	mil	ASTM D-374
Tack:	550	gm/cm <sup>2</sup>	ASTM D-2979

Shelf Life:

Two years, under standard storage and humidity conditions

PRODUCT DISCLAIMER

All labels and label material constructions are sold with the understanding that the purchaser has independently determined the suitability of each product for the application for which it is purchased. The seller disclaims any implied warranty of fitness of a product for a particular purpose. All materials should be tested thoroughly by the purchaser under end-user conditions to ensure they meet the requirements of a specific application.